

## 45 KVA GPW45Y SPECIFICATION SHEET

- EUV compliant
- Galvanised sound-attenuated enclosure
- Bunded base tank
- Fork pockets
- Voltage: 400/230 V
- Engine: Yanmar 4TNV98CT-IPGE
- Alternator: Mecc Alte ECO32 2S4 C
- Governor: Electronic
- Control Panel: Deep Sea



*Generator shown is indicative and may not be representative of equipment available at the time.*

Size kVA	Length (mm)	Width (mm)	Height (mm)	Weight Dry (kg)*	Fuel Capacity (Lt)	Sound Pressure Levels (dBA) @7m
45 kVA	2200	1020	1620	987	245	61

\*Weight with lube oil, no coolant, no fuel.



Running Time			Fuel Consumption		
50% Load (hrs)	75% Load (hrs)	100% Load (hrs)	50% Load (hrs)	75% Load (LPH)	100% Load (LPH)
47	32.5	21.5	5.2	7.43	10.55

**SOCKETS**

**3 x**

SINGLE PHASE  
32A

**1 x**

3 PHASE  
63A



**24/7 EMERGENCY 365 DAYS A YEAR >> 24/7 SUPPORT 365 DAYS A YEAR >> NATIONWIDE COVERAGE 365 DAYS A YEAR >>**

*The Company reserves the right, prior to the delivery date to substitute the equipment with an alternative providing no less power than stated above.*

**North West Depot**  
Stuart House, Haydock Lane,  
Haydock Industrial Estate,  
Merseyside  
WA11 9UH

**North East Depot**  
Middleplatt Road  
Immingham  
DN40 1AH

**West Midlands Depot**  
Diglis Trading Estate  
Navigation, Road, Worcester  
WR5 3DE

**East Anglia Depot**  
Stuart House, Hargham Road  
Shropham, Norfolk  
NR17 1DT

