

SafeGen Specification Sheet 30kVA

SafeGen
reducenoisepollution

- REDUCE NOISE & POLLUTION
- CONTROL PANEL
- CUSTOM BUILT
- GENERATOR & FUEL TANK
- SAFE & SECURE
- FORK LIFT POCKETS



SafeGen

Generator	Length (mm)	Width (mm)	Height (mm)	Fuel Tank Ltr	Weight Dry (kg)*
30KVA	3050	2438	2591	2100	4560



30kVA P33

Size kVA	Fuel Capacity (Lt)	50% Load (LPH)	75% Load (LPH)	100% Load (LPH)	Sound Pressure Levels (dBA) 7M 75% Load
30kVA	600	4	5.7	7.4	TBC

- BUNDED BASE TANK • FUEL EFFICIENT • ENGINE: PERKINS®
- ALTERNATOR: LEROY SOMER • GOVERNOR: MECHANICAL
- CONTROL PANEL: DCP10

Mains distribution with multiple sockets and cable available for hire

The Company reserves the right, prior to the delivery date to substitute the equipment with an alternative providing no less power than stated above.

NORTH WEST DEPOT >> T: 01744 419100

Park Industrial Estate, Gaskell Street, St Helens, WA9 1PX
enquiries@stuartgroup.info

EAST ANGLIA DEPOT & HQ >> T: 01953 454540

Stuart House, Hargham Road, Shropham, Norfolk, NR17 1DT
enquiries@stuartgroup.info

NORTH EAST DEPOT >> T: 01469 551230

Middleplatt Road, Immingham, DN40 1AH
enquiries@stuartgroup.info

WEST MIDLANDS DEPOT >> T: 01905 964499

Diglis Trading Estate, Navigation Road, Worcester, WR5 3DE
enquiries@stuartgroup.info

24/7 EMERGENCY 365 DAYS A YEAR >> 24/7 SUPPORT 365 DAYS A YEAR >> NATIONWIDE COVERAGE 365 DAYS A YEAR >>

