

300 KVA GPW300I/S5 SPECIFICATION SHEET


- EUV compliant
- Galvanised sound-attenuated enclosure
- Bunded base tank
- Fork pockets
- Voltage: 400/230 V
- Engine: FPT C87TEVP04
- Alternator: Leroy Somer LSA 46.3 L10
- Governor: Electronic
- Control Panel: Deep Sea
- AdBlue Tank: 80 litres



Generator shown is indicative and may not be representative of equipment available at the time.

Size kVA	Length (mm)	Width (mm)	Height (mm)	Weight Dry (kg)*	Fuel Capacity (Lt)	Sound Pressure Levels (dBA) @7m
300 kVA	4165	1500	2130	4540	800	67

*Weight with lube oil, no coolant, no fuel.



Hertz	Running Time			Fuel Consumption		
	50% Load (hrs)	75% Load (hrs)	100% Load (hrs)	50% Load (hrs)	75% Load (LPH)	100% Load (LPH)
50	25	16.5	12.5	31.8	47.6	63.6
60	21	14	10.5	37.5	56	75

SOCKETS

3 x SINGLE PHASE 32A

1 x 3 PHASE 63A

1 x 3 PHASE 125A



24/7 EMERGENCY 365 DAYS A YEAR >> 24/7 SUPPORT 365 DAYS A YEAR >> NATIONWIDE COVERAGE 365 DAYS A YEAR >>

The Company reserves the right, prior to the delivery date to substitute the equipment with an alternative providing no less power than stated above.

North West Depot
Stuart House, Haydock Lane,
Haydock Industrial Estate,
Merseyside
WA11 9UH

North East Depot
Middleplatt Road
Immingham
DN40 1AH

West Midlands Depot
Diglis Trading Estate
Navigation, Road, Worcester
WR5 3DE

East Anglia Depot
Stuart House, Hargham Road
Shropham, Norfolk
NR17 1DT

