


CD80D Hush Pac Specification Sheet

- Fully automatic priming from dry to 8.5 metres suction lift.
- Extensive application flexibility. It will handle sewage, slurries and liquids with solids up to 40 mm in diameter.
- Engine: Kubota Z482
- A Close-coupled centrifugal pump with Godwin Dri-Prime system mounted to a diesel engine or electric drive.



Pump shown is indicative and may not be representative of equipment available at the time.

Performance Curve



Specifications

Suction Connection	80 mm (3" BS10 Table 'D')		
Delivery Connection	80 mm (3" BS10 Table 'D')		
Max Capacity	96 m³/hr		
Max Head	36 metres		
Max Solids Handling	40 mm		
Max Impeller Diameter	166 mm		
Max Operating Temp	80 °C		
Max Working Pressure	4.0 bar		
Max Suction Pressure	2.8 bar		
Max Casing Pressure	6.0 bar		
Max Operating Speed	3000 rpm		
Running Speed	Distance		
	1	3	7
1400	63	58	53
2000	65	63	54
Fuel capacity (Full) 60 litres, (Usable) 55 litres			
Fuel consumption @ 2000 rpm BEP 1 litres/hour			
Weight: (Dry) 630 kg, (Wet) 725 kg			
Dimensions: (L) 1,621 x (W) 853 x (H) 1,333 mm			

Suction Lift Table

Total Suction Head (meters)	Total delivery head (meters)				
	3	7	9	11	14
	Output (m³/hr)				
3.0	65	60	52	40	10
4.6	63	55	45	-	-
6.1	55	45	30	-	-
7.6	45	35	15	-	-

The Company reserves the right, prior to the delivery date to substitute the equipment with an alternative providing no less power than stated above.



24/7 EMERGENCY 365 DAYS A YEAR >> 24/7 SUPPORT 365 DAYS A YEAR >> NATIONWIDE COVERAGE 365 DAYS A YEAR >>

North West Depot
Stuart House, Haydock
Lane, Haydock Industrial
Estate, Merseyside
WA11 9UH

North East Depot
Middleplatt Road
Immingham
DN40 1AH

West Midlands Depot
Diglis Trading Estate
Navigation, Road, Worcester
WR5 3DE

East Anglia Depot
Stuart House, Hargham Road
Shropham, Norfolk
NR17 1DT

